

Document number: PD-00005
Document name: Polarium Safety Data Sheet
Author(s): Henrik Lundgren
Revision: 11
Approved by: Sven Bergqvist
Created date: 2021-02-09
Approved date: 2022-05-19



Safety Data Sheet

Polarium Battery Cells and Modules

1. Product and Company Identification

Important Note: As a solid, manufactured article, exposure to hazardous ingredients is not expected with normal use. This battery is an article pursuant to 29 CFR 1910.1200 and, as such, is not subject to the OSHA Hazard Communication Standard requirement.

The information contained in this (Material) Safety Data Sheet contains valuable information critical to the safe handling and proper use of the product.

This (M)SDS should be retained and available for employees and other users of this product. Read Safety Data Sheet and installation manual before use.

Product identification

Lithium-ion battery

Synonyms

Lithium-ion Cell, Lithium-ion Battery, Li-ion Cell, Li-ion Battery

Supplier

Polarium Energy Solutions AB

Address

JAN STENBECKS TORG 17
SE-16440 KISTA, SWEDEN
Ph. +46 8 5454 4000

Polarium AS SA DE CV

Address

CARR CHAPALA 9999 INT 1-B
45672, ZAPOTE DEL VALLE
TLAJOMULCO DE ZUNGIA
JALISCO, MEXICO
Ph. +52 1(33) 1602 8821

Polarium Vietnam Company Limited

Address

JUPITER LAND PLOT CN4D, DEEP C 2B INDUSTRIAL ZONE, DINH VU
CAT HAI ECONOMIC ZONE, DONG HAI 2 WARD
HAI AN DISTRICT, HAI PHONG CITY, VIETNAM
Ph. +84 33 881 1894

Emergency response telephone

- North America (United States of America, Canada, Puerto Rico, and the U.S. Virgin Islands): For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Toll Free:
1-800-424-9300/ +1 703-527-3887 CCN 869548
- Shipments of hazardous materials within the listed countries should reference ChemTel's in-county phone numbers: Australia: +1-300-954-583, Brazil: 0-800-591-6042, China: 400-120-0751
- India: 000-800-100-4086
- Mexico: 800-099-0731
- Application outside of the US, Canada, Puerto Rico and the U.S. Virgin Islands and other listed countries: Call Chemtel: +1-813-248-0585

Further Information

Nominal voltage: 46-51 V (Module), 3.2-3.7 V (Cell)

Capacity: 8-300 Ah (Module), 2-100 Ah (Cell)

Energy: 400-15500 Wh (Module), 7-320 Wh (Cell)

Anode (negative electrode): based on Graphite or Graphite and blended Silicon

Cathode (positive electrode): based on Lithiated Metal Oxide (mainly Nickel Oxide) or Lithium Iron Phosphate

Remark

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Polarium Energy Solutions AB makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

2. Hazards Identification

Classification of the substance or mixture

Preparation Hazards and Classification: The product is a Lithium ion cell or battery and is therefore classified as an article and is not hazardous when used according to the recommendations of the manufacturer. The hazard is associated with the contents of the cell or battery. Under recommended use conditions, the electrode materials and liquid electrolyte are non-reactive provided that the cell or battery integrity remains, and the seals remain intact. The potential for exposure should not exist unless the cell or battery leaks, is exposed to high temperatures or is mechanically, electrically, or physically abused/damaged. If the cell or battery is compromised and starts to leak, based upon the battery ingredients, the contents are classified as Hazardous.

Hazard Summary

Physical hazards: Not classified for physical hazards.

Health hazards: Not classified for health hazards.

Environmental hazards: Not classified for hazards to the environment.

Specific hazards: Exposure to contents of an open or damaged cell or battery: contact with this material will cause burns to the skin, eyes and mucous membranes. May cause sensitization by skin contact.

Main Symptoms: Symptoms include itching, burning, redness and tearing.

Hazardous Materials Information Label (HMIS)

Health: 0

Flammability: 1

Physical Hazard: 0

NFPA Hazard Ratings

Health: 0

Flammability: 1

Reactivity: 0

Unique Hazard: None

Other Hazards

Appearance

Color and Odor: Solid object with no odor.

Primary Route(s) of Exposure: These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell or pack is mechanically, thermally, electrically or physically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by inhalation, ingestion, eye contact and skin contact.

Potential Health Effect(s):

Acute (short term): See Chapter 8 for exposure controls. In the event that this cell or pack has been ruptured, the electrolyte solution contained within the cell would be corrosive and can cause burns to skin and eyes.

Inhalation: Inhalation of materials from a sealed cell is not an expected route of exposure. Vapors or mists from a ruptured cell may cause respiratory irritation.

Ingestion: Swallowing of materials from a sealed cell is not an expected route of exposure. Swallowing the contents of an open cell can cause serious chemical burns to mouth, esophagus, and gastrointestinal tract.

Skin: Contact between the cell and skin will not cause any harm. Skin contact with the contents of an open cell can cause severe irritation or burns to the skin.

Eye: Contact between the cell and the eye will not cause any harm. Eye contact with the contents of an open cell can cause severe irritation or burns to the eye.

Chronic (long term): See Chapter 11 for additional toxicological data.

Interactions with other chemicals: Immersion in high conductivity liquids may cause corrosion and breaching of the cell or battery enclosure. The electrolyte solution inside of the cells may react with alkaline (basic) materials and present a flammability hazard.

Potential Environmental Effects: Not Available.

Hazard labels



GHS precautionary statements

<p>Precautionary Statement(s) Prevention</p>	<p>P102: Keep out of reach of children. P103: Read label prior to use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/sparks/open flames/hot surfaces –No smoking. P234: Keep only in original container. P254: Wash hands thoroughly after handling.</p>
<p>Response (If cell/battery leaks)</p>	<p>P260: Do not breathe vapor or spray. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301/330/331: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. P303/361/353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304/340: If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305/351/338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P363: Wash contaminated clothing before reuse. P370: In case of fire: Use carbon dioxide, dry chemical or water extinguisher.</p>
<p>Storage (Store as indicated in Section 7)</p>	<p>P402: Store in a dry place. P405: Store locked up. P410: Protect from sunlight.</p>
<p>Disposal</p>	<p>P406: Store any spilled/leaking electrolyte material in a corrosive resistant container with a resistant inner liner. P501: Dispose of batteries in accordance with applicable hazardous waste regulations.</p>

3. Composition/information on ingredients

Hazardous components

CAS-No.	Chemical name	Quantity (wt%)
1307-96-6 15365-14-7	Includes one of the following positive electrodes: Lithium transition metal oxide Lithium Iron Phosphate	<50%
1313-13-9	Aluminium	<20%
7440-50-8	Copper	<10%
7439-89-6	Steel	<15%
7440-44-0 7440-21-3	Includes one or more of the following negative electrodes: Carbon Silicon	<40%
21324-40-3	Lithium hexafluorophosphate	<5%
96-49-1 623-53-0 616-38-6	Includes one or more of the following electrolyte solvents: Ethylene Carbonate Ethyl methyl Carbonate Dimethyl Carbonate	<20%
24937-79-9	Polyvinylidene fluoride (PVdF)	<1%

Further Information

Because of the cell structure the hazardous materials will not be available if used properly.

Mercury content: Hg < 0.1 mg/kg

Cadmium content: Cd < 1 mg/kg

Lead content: Pb < 10 mg/kg

4. First Aid Measures

Description of first aid measures

The hazardous components of this cell or battery are contained within a sealed unit. The following measures are only applicable if exposure has occurred to components when a cell or battery leaks, is exposed to high temperatures or is mechanically, electrically, or physically abused/damaged. The hazardous contents are caustic alkaline electrolytes contained in cells with Lithium Metal Oxide positive electrode, Carbon negative electrode, and Polyvinylidene fluoride binders.

Ingestion: Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Quickly transport victim to an emergency care facility.

Eye contact: If eye contact with contents of an open cell occurs, immediately flush the contaminated eye(s) with water. Quickly transport victim to an emergency care facility.

Skin Contact: Immediately flush with water. If irritation or pain persists, seek medical attention.

Inhalation: Remove the patient from exposure into fresh air, seek medical attention.

Protection for first aiders

Do not enter corrosive vapor contaminated areas without a respirator or self-contained breathing apparatus. Wear adequate personal protective equipment as indicated in Chapter 8.

First aid facilities

Eye wash bottle, fountain, safety showers or at least a source of running water are required in the area where the product is used.

Most important symptoms & effects, acute & delayed, caused by exposure

Acute: The contents of the battery are rated as corrosive. Ingestion of the electrolyte could lead to severe gastrointestinal tract irritation with nausea, vomiting and potentially burns. Inhalation of vapors may lead to severe irritation of the mouth and upper respiratory tract with a burning sensation, pain, burns and inflammation in the nose and throat; there may also be coughing or difficulty breathing. Eye contact may lead to severe eye irritation or in worst case scenario irreversible damage and possible eye burns. Skin contact may lead to irritation and possible skin burns.

Chronic: Skin contact may aggravate/exacerbate existing skin conditions, such as dermatitis. Chronic inhalation may lead to the same symptoms as listed for acute inhalation above.

Indication of any immediate medical attention and special treatment needed

Advice to doctor: Treat symptomatically if the person comes into contact with the corrosive electrolyte liquid contents of a damaged battery.

5. Fire Fighting Measures

Suitable extinguishing media

Cold water and dry powder in large amount are applicable.

Use metal fire extinction powder or dry sand if only few cells are involved.

Special hazards arising from the chemical

May form hydrofluoric acid if electrolyte comes into contact with water. In case of fire, the formation of the following flue gases cannot be excluded: Hydrogen fluoride (HF), Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

If possible, remove cell(s) from firefighting area. If heated above 125°C, cell(s) can explode/vent. Cell is not flammable but internal organic material will burn if the cell is incinerated.

6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures

As an immediate precautionary measure, isolate spill, or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed areas before entering. Wear adequate personal protective equipment as indicated in Section 8.

Environmental precautions

Absorb spilled material with non-reactive absorbent such as vermiculite, clay, or earth. Prevent from migration into soil, sewers, and natural waterways – inform local authorities if this occurs.

Methods and material for containment and cleaning up

Evacuate spill area immediately and remove sources of ignition. Do NOT touch spilled material. Cleanup personnel must be trained in the safe handling of this product. Spills may be absorbed on non-reactive absorbents such as vermiculite. Place cells or batteries into individual plastic bags and then place into appropriate containers and close tightly for disposal. Ensure that cleanup procedures do not expose spilled material to any moisture. Immediately transport closed containers outside. Lined steel drums are suitable for storage of damaged cells or batteries until proper disposal can be arranged.

7. Handling and Storage

Precaution for Handling

Avoid short circuiting the cell. Avoid mechanical damage of the cell. Do not open or disassemble. Keep away from open flames, hot surfaces, and sources of ignition.

Condition for storage

Store in well ventilated, dry conditions at approximately 20±5 °C and 20-60 % state of charge (Open circuit voltage of approximately 3.6-3.9 V/cell for Nickel-based products, 3.2-3.3 V/cell for Iron-based products). Keep in closed original container when not in use.

The boxes and batteries are designed for storage in indoor environments (except for outdoor rated batteries). Do not store in wet or moist environments.

8. Exposure Controls/Personal Protection

Exposure Control Measures

Exposure Limit Values: Airborne exposures to hazardous substances are not expected when the cells or batteries are used for their intended purposes. Exposure standards are not applicable to the sealed articles.

Biological Monitoring: Not applicable.

Control Banding: Not applicable.

Recommended monitoring procedures: Follow standard monitoring procedures.

Derived no-effect level (DNEL) and minimal effect level (DMEL): Not applicable.

Predicted no-effect concentrations (PNECs): Not applicable.

Engineering Controls

Engineering Controls: Special ventilation is not required when using these products in normal use scenarios. Ventilation is required if there is leakage from the cell or battery.

Individual Protection Measures

Eye and Face protection: Eye protection is not required when handling cells or batteries during normal use. Wear safety glasses/goggles if handling a leaking or ruptured cell or battery.

Skin (Hand) protection: Hand protection is not required when handling the cell or battery during normal use. PVC gloves are recommended when dealing with a leaking or ruptured cell or battery.

Skin (clothing) protection: Skin protection is not required when handling the cell or battery during normal use. Wear long sleeved clothing to avoid skin contact if handling a leaking or ruptured cell or battery. Soiled clothing should be washed with detergent prior to re-use.

Respiratory protection: During routine operation, a respirator is not required. However, if dealing with an electrolyte leakage and irritating vapors are generated, an approved half face inorganic vapor and gas/acid/particulate respirator is required.

Thermal Protection: Not applicable.

Other Protective Equipment: Have a safety shower or eye wash station readily available.

Hygiene Measures

Do not eat, drink, or smoke in work areas. Avoid storing food, drink, or tobacco near the product. Practice and maintain good housekeeping.

Environmental exposure controls

Avoid release to the environment.

9. Physical and Chemical Properties

Appearance

Form: Solid

Color: Various

Odor: Odourless

Important health, safety, and environmental information

pH value: Not applicable.

Flash point: Not applicable.

Lower explosion limits: Not applicable.

Vapour pressure: Not applicable.

Density: Not applicable.

Water solubility: Insoluble

Ignition temperature: Not applicable.

10. Stability and Reactivity

Stability

Stable.

Conditions to avoid

Keep away from open flames, hot surfaces, and sources of ignition. Do not puncture, crush, or incinerate.

Materials to avoid

No materials to be especially mentioned.

Hazardous decomposition products

In case of open cells, there is the possibility of hydrofluoric acid and carbon monoxide release.

Possibility of Hazardous Reactions

Will not occur.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological Information

Information on toxicological effects

The hazardous components of the cell or battery are contained within a sealed unit. Under recommended use conditions, the electrode materials and liquid electrolyte are non-reactive provided that the cell or battery integrity remains, and the seals remain intact. The potential for exposure should not exist unless the battery leaks, is exposed to high temperature or is mechanically, electrically, or physically abused/damaged. The following toxicology data is in respect to if a person comes into contact with the electrolyte.

Acute Toxicity

Swallowed: The electrolyte contained within the cell or battery is a corrosive liquid. Ingestion of this electrolyte would be harmful. Swallowing may result in nausea, vomiting, diarrhea, abdominal pain, and chemical burns to the gastrointestinal tract. During normal usage ingestion should not be a means of exposure.

Eye: The electrolyte contained within the cell or battery is a corrosive liquid and it is expected that it would cause irreversible damage to the eyes. Contact may cause corneal burns. Effects may be slow to heal after eye contact. Correct handling procedures incorporating appropriate eye protection should minimize the risk of eye irritation.

Skin: The electrolyte contained within the cell or battery is a corrosive liquid and it is expected that it would cause skin burns or severe irritation to the skin if not washed off immediately. Correct handling procedures should minimize the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

Inhaled: Inhalation of vapors from a leaking cell or battery is expected to cause severe irritation of the mouth and upper respiratory tract with a burning sensation, pain, burns and inflammation in the nose and throat; there may also be coughing or difficulty breathing.

Skin Corrosion/Irritation: The electrolyte contained within the cell or battery is classified as a corrosive liquid and is expected to exhibit Dermal Corrosivity/Irritation.

Serious Eye Damage/Irritation: The electrolyte contained within the cell or battery is classified as a corrosive liquid and is expected to exhibit serious Damage/Corrosivity.

Respiratory or Skin Sensitization: The electrolyte contained within the cell or battery is not expected to be a skin sensitizer according to OECD test 406, based on the available data and the known hazards of the components. The electrolyte contained within the battery is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.

Germ Cell Mutagenicity: The electrolyte contained within the cell or battery is not expected to be mutagenic according to test such as OECD tests 471, 475, 476, 478 and 479, based on the available data and the known hazards of the components.

Carcinogenicity: The electrolyte contained within the cell or battery is not expected to be a carcinogen. The cathode contains Cobalt and Nickel components. These components are classified as IARC 2B –possibly carcinogenic to humans, however they do not pose a threat when contained in the cell or battery sealed unit. **Reproductive Toxicity:** The electrolyte contained within the cell or battery is not expected to be a

reproductive hazard according to test such as OECD tests 414 and 421, based on the available data and the known hazards of the components.

Specific Target Organ Toxicity (STOT) –Single Exposure: The electrolyte contained within the cell or battery is corrosive and is expected to cause respiratory irritation by inhalation. Inhalation of vapors may lead to severe irritation of the mouth and upper respiratory tract with a burning sensation, pain, burns and inflammation in the nose and throat; there may also be coughing or difficulty breathing.

Specific Target Organ Toxicity (STOT) –Repeated Exposure: The cells or batteries are not expected to cause organ damage from prolonged or repeated exposure according to tests such as OECD tests 410 and 412, based on the available data and the known hazards of the components.

12. Ecological Information

Ecological injuries are not known or expected under normal use. Do not flush into surface water or sanitary sewer system.

13. Disposal Considerations

Advice on disposal

For recycling consult manufacturer.

Contaminated packaging

Disposal in accordance with local regulations.

14. Transport Information

UN Number: 3480

UN Proper Shipping Name: Lithium-Ion Batteries

Transport Hazard Class: 9

Packing Information:

Road (ADR): P903

Rail (RID): P903

Inland waterways (ADN): P903

Sea (IMDG): P903

Air (IATA/ ICAO): PI965, Section IA (Modules)

PI965 Section IB, Section II or Section IA (Cells)

The boxes are designed for transportation in weather protected environments. Do not transport on open flat decks.

15. Regulatory Information

Australia and New Zealand

SUSMP: Not applicable

AICS: All ingredients are on the AICS list.

HSNO Approval number: Not applicable

HSNO Group Title: Not applicable

NOHSC:10008 Risk Phrases:

R34 -Causes Burns.

NOHSC:1008 Safety Phrases:

S1 –Keep locked up.

S2 –Keep out of reach of children.

S23 –Do not breathe vapor.

S24/25 –Avoid contact with skin and eyes.

S26 –In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27/28 –After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of water.

S36/37/39 –Wear suitable protective clothing, gloves and eye/face protection.

S56 –Dispose of this material and its container at hazardous waste or special waste collection point.

S62 –If swallowed, DO NOT induce vomiting: seek medical advice immediately and show this container or label.

S64 –If swallowed, rinse mouth with water (Only if the person is conscious).

Canadian Federal Regulations

These products have been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification: Not Controlled, manufactured article.

New Substance Notification Regulations: Lithium hexafluorophosphate is listed on the Non-Domestic Substance List(NDSL). All other ingredients in the product are listed, as required, on Canada's Domestic Substances List (DSL).

National Pollutant Release Inventory (NPRI) Substances: These products do not contain any NPRI chemicals.

Chinese regulations

General Rule for Classification and Hazard Communication of Chemicals (GB 13690-2009): Specifies the classification, labeling and hazard communication of chemicals in compliance with the GHS standard for chemical production sites and labeling of consumer goods.

General Rule for Preparation of Precautionary Labels for Chemicals (GB 15258-2009): Specifies the relevant application methods of precautionary labels for chemicals.

Safety Data Sheet for Chemical Products Content and Order of Sections (GB/T 16483-2008)

The European Union

EC Classification for the Substance/Preparation

These products are not classified as hazardous according to Regulation (EC) No. 1272/2008. Keep out of the reach of children.

EU Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended: Aluminum (CAS 7429-90-5)

Other EU Regulations

This Safety Data Sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Japanese regulations

Japanese Industrial Standards (JIS) JIS Z 7253:2012

Waste disposal and public cleaning law

Law for Promotion of Effective Utilization of Resources

Tawainese regulations

Regulation of Labelling and Hazard Communication of Dangerous and Harmful Materials: Labeling requirements and other relevant provision of chemicals, this product is not classified as dangerous goods.

Toxic Chemicals Substance Control Law: Not Listed.

CNS 1030016 Safety of primary and secondary lithium cells and batteries during transport.

United States Federal and State Regulations

TSCA Status: All ingredients in these products are listed on the TSCA inventory.

OSHA: These products do not meet criteria as per Part 1910.1200, manufactured article.

SARA EPA Title III: None

Sec. 302/304: None

Sec. 311/312: None

Sec. 313: None

CERCLA RQ: None

16. Other Information

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations. The data for the

hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.

Revision	Date	Revision change	Author(s)
1	2021-02-09	First issue	Henrik Lundgren
2	2021-03-26	Added BKB90290/1 and BKB90290/2 to list. Removed variants of same battery from list.	Henrik Lundgren
3	2021-05-06	Added new products to list of applicable products.	Henrik Lundgren
4	2021-10-13	Added ChemTel emergency phone number Merged with cell SDS (PD-00006, PD-00007) Added new products to list of applicable products Added Swedish and Vietnamese company locations	Henrik Lundgren
5	2022-01-12	Added new products to list of applicable products	Johan Hagberg
6	2022-02-11	Added text about variants of the same battery	Henrik Lundgren
7	2022-03-14	Changed emergency contact information for North America to CHEMTREC Added HVS module and Gen 6.1	Henrik Lundgren
8	2022-03-18	Added text on storage and transportation environmental conditions.	Henrik Lundgren
9	2022-04-13	Added SLBO products to list.	Henrik Lundgren
10	2022-04-19	Added new products to list of applicable products.	Johan Hagberg
11	2022-05-19	Added new products to list of applicable products.	Johan Hagberg

Please contact Polarium for the latest revision of the safety data sheet.

Applicable Modules

Note: Variants of the same battery (e.g. with numbered or other suffixes (e.g. 1, see SLB48-250-146-21) are covered by their parent battery without suffix, i.e. SLB48-250-146-2 in the example)

Commercial Product Name
B48-180-228-1U
BKB90271/13
BKB90271/131
BKB90271/21
BKB90271/211
BKB90271/22
BKB90271/221
BKB90290/1
BKB90290/2
CS7180210.00
CS7180211.00
CS7180212.00
CS7180213.00
CS7180214.00
CS7180215.00
CS7180216.00
CS7180217.00
CS7180233.00
SLB48-008-OUT-2
SLB48-043-OUT-2
SLB48-050-124-1
SLB48-050-124-1U
SLB48-050-124-2
SLB48-050-143-5
SLB48-100-135-5
SLB48-100-144-1
SLB48-100-144-1U
SLB48-100-144-2
SLB48-100-145-5
SLB48-100-226-1
SLB48-100-226-1U
SLB48-100-226-2
SLB48-110-225-1

Commercial Product Name
SLB48-150-146-1
SLB48-150-146-2
SLB48-150-146-5
SLB48-180-228-1U
SLB48-200-146-1
SLB48-200-146-2
SLB48-200-147-1
SLB48-200-147-2
SLB48-200-228-1U
SLB48-200-228-1
SLB48-210-146-1
SLB48-210-146-2
SLB48-250-146-1
SLB48-250-146-2
SLB48-250-147-1
SLB48-250-147-2
SLB48-300-147-1
SLB48-300-147-2
B48-180-228-1U
HVM-200-228-1